

# Testing Method – OpenPLC

*A list and description of how to test Thurst 2: Open PLC Project.*

- **Unconnected**
  - *Future Work - Develop tool for testing this type*
- **Connected**
  - *Analog*
    - Using AdvancedHMI, we are creating a simulated blinking LED and changing the frequency of the blinking LED using buttons on AdvancedHMI.
  - *Digital*
    - Using AdvancedHMI, we are creating a simulated blinking LED ( 0 – OFF  
1 – ON)
- **Unknown**
  - *Ethersploit -> send\_raw\_pccc [data]*
    - Using Cygwin, run this exploit tool just sends raw data to the PLC.
      - *./ethersploit*
      - *Connect 127.0.0.1*
      - *Send\_raw\_pcc [data]*

## **\*Programs and Tools Used for Testing:**

- *OpenPLC Runtime – Virtual PLC*
- *Cygwin – Application that allows Linux native apps on Windows*
- *Wireshark – Packet capture tool to verify contents are sending and receiving*
- *AdvancedHMI – HMI that was used to test usability and application*
  - *Replace the folder “AdvancedHMI” with the folder from Google Drive*
  - <https://drive.google.com/drive/folders/1tPYGuvh1GNW0IMSPyFzmMyou3Hzl3V4g>
  - *Select the form in AdvancedHMI from the “AllTest” folder*

# AdvancedHMI Tests

*A description of the successfully tested functions and how to set up AdvancedHMI in order to test those functions. All testing and verification can be done with the ladder logic file “alltest3.st” and with the single Advanced HMI setup provided. Wireshark is also used to verify the correct format of the packets.*

## Functions

PCCC supports three different overarching functions. Protected Logical Read is used to read data from memory. Protected Logical Write is used to write byte size data into memory. Protected Logical Write with Mask is used to write bitwise data into memory.

## File Types & Numbers

The PCCC protocol stores data in sections of memory blocked off in “files”. Each of these sections has a corresponding File Type and File Number. The four file types implemented in OpenPLC are Input Logical by Slot, Output Logical by Slot, Integer, and Float.

## Read Digital Output

**Description of Test:** The PLC returns a binary value from the digital output memory.

**Function Code** 0xA2      **File Type** 0x8B      **File Number** 0x00

**Ladder Logic File:** alltest.st

### **AdvancedHMI Interface Components List:**

- Driver – EthernetIPforSLCMicroCom1
- Basic Indicator – Reads from the Address either a 1 or 0
- Basic Button ON – Writes a 1
- Basic Button OFF – Writes a 0

**Drive Location:** <https://drive.google.com/drive/folders/1ouMFUaN8jH8vUa8VN8xtN5qIWeaL2NJB>

# Read Digital Input

**Description of Test:** The PLC returns a binary value from the digital input memory.

**Function Code** 0xA2      **File Type** 0x8C      **File Number** 0x01

**Ladder Logic File:** alltest.st

## **AdvancedHMI Interface Components List:**

- Driver – EthernetIPforSLCMicroCom1
- Basic Indicator – Reads from the Address either a 1 or 0
- Basic Button ON – Writes a 1
- Basic Button OFF – Writes a 0

**Drive Location:** <https://drive.google.com/drive/folders/1ouMFUaN8jH8vUa8VN8xtN5qIWeaL2NJB>

# Read Integer

**Description of Test for Analog:** The PLC return an integer value from memory.

**Function Code** 0xA2      **File Type** 0x89      **File Number** 0x07

**Ladder Logic File:** alltest.st

## **AdvancedHMI Interface Components List: Integer (Bottom Four Labels)**

- Driver – EthernetIPforSLCMicroCom1
- Basic Label – Keypad -> Double Click Label “Int1” (Writes)
- Basic Label – Keypad -> Double Click Label “Int2” (Writes)
- Basic Label – Number Display Above Int1 -> Int1 Value (Reads)
- Basic Label – Number Display Above Int2-> Int2 Value (Reads)

**Drive Location:** <https://drive.google.com/drive/folders/1ouMFUaN8jH8vUa8VN8xtN5qIWeaL2NJB>

# Read Float

**Description of Test for Analog:** The PLC return a float value from memory.

**Function Code** 0xA2      **File Type** 0x8A      **File Number** 0x08

**Ladder Logic File:** alltest.st

**AdvancedHMI Interface Components List: Floating Point (Top Three Labels)**

- Driver – EthernetIPforSLCMicroCom1
- Basic Label – Keypad -> Double Click Label “Float1” (Writes)
- Basic Label – Number Display Top Left -> Float1 Value (Reads)
- Basic Label – Number Display Top Right -> Float1 Value + 10.0 (Reads)

**Drive Location:** <https://drive.google.com/drive/folders/1ouMFUaN8jH8vUa8VN8xtN5qIWeaL2NJB>

# Write Digital Output

**Description of Test:** The PLC stores a binary value into digital output memory.

**Function Code** 0xAB      **File Type** 0xAB      **File Number** 0x00

**Ladder Logic File:** alltest.st

**AdvancedHMI Interface Components List: analogint.st**

- Driver – EthernetIPforSLCMicroCom1
- Basic Indicator – Reads from the Address either a 1 or 0
- Basic Button ON – Writes a 1
- Basic Button OFF – Writes a 0

**Drive Location:** <https://drive.google.com/drive/folders/1ouMFUaN8jH8vUa8VN8xtN5qIWeaL2NJB>

# Write Integer

**Description of Test for Analog:** The PLC stores an integer value into memory.

**Function Code** 0xAA

**File Type** 0x89

**File Number** 0x07

**Ladder Logic File:** alltest.st

## **AdvancedHMI Interface Components List: Integer (Bottom Four Labels)**

- Driver – EthernetIPforSLCMicroCom1
- Basic Label – Keypad -> Double Click Label “Int1” (Writes)
- Basic Label – Keypad -> Double Click Label “Int2” (Writes)
- Basic Label – Number Display Above Int1 -> Int1 Value (Reads)
- Basic Label – Number Display Above Int2-> Int2 Value (Reads)

**Drive Location:** <https://drive.google.com/drive/folders/1ouMFUaN8jH8vUa8VN8xtN5qiWeaL2NJB>

# Write Float

**Description of Test for Analog:** The PLC stores a float value into memory.

**Function Code** 0xA2

**File Type** 0x8A

**File Number** 0x08

**Ladder Logic File:** alltest.st

## **AdvancedHMI Interface Components List: Floating Point (Top Three Labels)**

- Driver – EthernetIPforSLCMicroCom1
- Basic Label – Keypad -> Double Click Label “Float1” (Writes)
- Basic Label – Number Display Top Left -> Float1 Value (Reads)
- Basic Label – Number Display Top Right -> Float1 Value + 10.0 (Reads)

**Drive Location:** <https://drive.google.com/drive/folders/1ouMFUaN8jH8vUa8VN8xtN5qiWeaL2NJB>




Figure 1: Reading Digital Inputs & Outputs with LED Indicators. Writing Digital Outputs with push buttons

```
▼ PCCC Response Data
  Response Code: 0x4f
  Status: Success (0x00)
  Transaction Code: 0x409e
  ▼ Function Specific Response Data
    Data: 0700
```

0000	00 00 00 00 00 00 00 00	00 00 00 00 08 00 45 00
0010	00 67 56 45 40 00 80 06	00 00 7f 00 00 01 7f 00
0020	00 01 af 12 cd 2a a7 86	20 cf d3 d0 52 68 50 18
0030	08 02 aa 52 00 00 70 00	27 00 6e 81 7f f1 00 00
0040	00 00 00 00 00 00 00 00	00 00 00 00 00 00 00 00
0050	00 00 00 00 02 00 a1 00	04 00 5a f0 b8 01 b1 00
0060	13 00 9e 40 cb 00 00 00	07 41 52 43 48 49 45 4f
0070	00 9e 40 07 00	

Figure 2: Response to a Read Input Logical by Slot request for 2 bytes. The first 3 least significant bits are all set to 1. (Notice the little endian format of the two bytes)




Figure 3: Reading Integers along the top row. Writing an integer value with the keypad.

▼ PCCC Response Data  
Response Code: 0x4f  
Status: Success (0x00)  
Transaction Code: 0x4039  
▼ Function Specific Response Data  
Data: 030002000500060002000c00

0000	00	00	00	00	00	00	00	00	00	00	00	08	00	45	00	
0010	00	7b	25	79	40	00	80	06	00	00	7f	00	00	01	7f	00
0020	00	01	af	12	e7	c8	84	66	45	9f	84	7e	0a	20	50	18
0030	08	01	93	67	00	00	70	00	3b	00	fc	43	cb	95	00	00
0040	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
0050	00	00	00	00	02	00	a1	00	04	00	5a	f0	b8	01	b1	00
0060	1d	00	39	40	cb	00	00	00	07	41	52	43	48	49	45	4f
0070	00	39	40	03	00	02	00	05	00	06	00	02	00	0c	00	0c
0080	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00

Figure 4: Response to Read Integer with for 12 Bytes.




Figure 5: Reading Floats along the top row. Writing a float value with the keypad.




Figure 6: Writing a Float value.